

Product Specifications

FlashLink Cold Chain USB In-Transit Logger



Recording Period	75 Days
Logging Interval	28 min, 16 sec
Measurement Range	-40°C to 50°C
Temperature Resolution	0.1°C
Accuracy	±0.5°C from -10°C to 25°C ±1.0°C above 25°C ±1.0°C below -10°C
Data Capacity	7920 points
Data Download Time	5 seconds typical for 3823 points
Battery	Coin Cell Lithium Battery
Dimension	1.575 in x 3.189 in x .575 in (40mm x 81mm x 13mm)
Casing	ABS plastic
Weight	1.3 oz. (36 grams)
Shock Resistance	Withstands 3-foot (1 meter) drop to hard surface
Certification	CE Mark, NIST traceable, ROHS Compliant
Display	°C Scale on LCD, Red LED Alarm
FAA Compliance	RTCA/DO-160
IP Rating	IP54 (with silicon cap on)
Storage conditions	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
System Requirements	Windows PC with current operating system, Adobe Reader, FlashPDF software
Download Requirements	Direct USB connection



Model 20996

- Ideal for export shipments
- Download to check temperature at each stopping point on a shipping route
- Continues to record data after downloading, until memory is full
- Logs temperature history all the way to final destination
- Patented Shadow Log® feature guarantees data even if operator fails to start the unit
- Trip history statistics available on LCD
- Direct USB connection, no cradle, reader or adapter needed
- Download data as PDF report using free FlashPDF software with multi-language options

High visibility shipping sleeve



Patent No. 6,088,514

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS 20996 18C1

