

Electronic Circular Chart Temperature Recorder

Product Specifications

Temperature Range Selectable	-40°F to 30°F / -20°F to 50°F / 50°F to 120°F -40°C to 0°C / -30°C to 10°C / 10°C to 50°C
Chart Speed Selectable	6 hours, 24 hours, 7 days, 31 days
Chart Speed Accuracy	±1%
Chart Diameter	6 inches (152.4mm)
Temperature Display	3 digit LED 0.5 inches high
Temperature Accuracy	±2°F (±1°C)
Temperature Sensor	Stainless steel probe 2 7/8"L x 1/4"D solid state integrated circuit, on 15' ft. cord
Recording Pen	Ink type
Power Supply	120 VAC, 50/60 Hz., (220/240 VAC, 50 Hz. optional)
Battery Backup	Holder for 8 alkaline AA cells (batteries not included)
Battery Life	48 hours
Operating Temperature	32°F to 120°F (0°C to 49°C)
Relative Humidity	96% maximum
Dimensions	9 in x 6.875 in x 2.33 in (228mm x 174mm x 59mm)
Weight	1 lbs 12 oz. (0.7 kg.)



Model 14010

(°C) 220v

Model 14011

(°C) 110v

Model 14012

(°F) 110v

- Select single or continuous chart rotation
- Stainless steel probe allows you to measure the temperature of air, gas, liquids, powders, and semi-solids
- Back-up batteries allow continuous function (up to 48 hrs) during power failures

Recorder Accessories

14597	Probe
14598	Blue Pen
14599	Red Pen

Chart Speeds

Temperature Ranges	12 Hours	24 Hours	7 Days	31 Days
-20 to +120°F	14600	14601	14602	14603
-20 to +50°F	14604	14605	14606	14607
+40 to +110°F	14608	14609	14610	14611
-30 to +50°C	14612	14613	14614	14615
-30 to +10°C	14616	14617	14618	14619
+5 to +45°C	14620	14621	14622	14623

*NOTE: For 1.5 Hour, 3 Hour and 6 Hour readings, use the 12 Hour charts.

DeltaTRAK manufactures products under an ISO 9000 registered quality management system

SS0021 13F1

