

Product Specifications

Digital Display Environmental Temperature Recorder



Low Temp Range	-20°F to 100°F (-28°C to 38°C)
High Temp Range	30°F to 150°F (0°C to 65°C)
Accuracy	Chart and Scale: $\pm 1.8^\circ\text{F}$ ($\pm 1.0^\circ\text{C}$) LCD: $\pm 1.8^\circ\text{F}$ (-20°C to 165°C), $\pm 1.0^\circ\text{C}$ (-7°C to 74°C)
LCD Display/Chart Window	1.5" x 0.5" (3.8cm x 1.3cm)/2" x 2.8" (5cm x 7.1cm)
Sensor	Bi-metal coil/thermistor
Chart	Pressure-sensitive 36-inch strip
Drive	Solid-state quartz motor
Certification	CE mark, RoHS compliant
Battery	AAA alkaline (3-year shelf life; 1 to 2 years operating life)
Weight	1.1 lb (500 grams)
Dimensions	4in. x 7in. x 2.25in. (10.2cm x 17.8cm x 5.72cm)
Casing Materials	High impact ABS



Models	3-Day	10-Day	62-Day
High Range °C	18020	18024	18030
High Range °F	18021	18025	18031

	3-Day	10-Day	31-Day
Low Range °C	18022	18026	18028
Low Range °F	18023	18027	18029

DeltaTrak manufactures products under an ISO 9000 registered quality management system

- Highly visible LCD display and large window for viewing current and recently chart recorded temperature data
- Reusable, light weight, compact and battery operated, can be wall-mounted, or hung from a loop
- Wall-mounting bracket, screws and QC chart provided
- 12 models in °F and °C scales and two temperature ranges for 3-Day, 10-Day, 31-Day and 62-Day time intervals

SS0033 13K1

