

# Product Specifications

## Digital Display Environmental Temperature Recorder



<b>Low Temp Range</b>	-20°F to 100°F (-28°C to 38°C)
<b>High Temp Range</b>	30°F to 150°F (0°C to 65°C)
<b>Accuracy</b>	Chart and Scale: $\pm 1.8^\circ\text{F}$ ( $\pm 1.0^\circ\text{C}$ ) LCD: $\pm 1.8^\circ\text{F}$ (-20°C to 165°C), $\pm 1.0^\circ\text{C}$ (-7°C to 74°C)
<b>LCD Display/Chart Window</b>	1.5" x 0.5" (3.8cm x 1.3cm)/2" x 2.8" (5cm x 7.1cm)
<b>Sensor</b>	Bi-metal coil/thermistor
<b>Chart</b>	Pressure-sensitive 36-inch strip
<b>Drive</b>	Solid-state quartz motor
<b>Certification</b>	CE mark, RoHS compliant
<b>Battery</b>	AAA alkaline (3-year shelf life; 1 to 2 years operating life)
<b>Weight</b>	1.1 lb (500 grams)
<b>Dimensions</b>	4in. x 7in. x 2.25in. (10.2cm x 17.8cm x 5.72cm)
<b>Casing Materials</b>	High impact ABS



Models	3-Day	10-Day	62-Day
<b>High Range °C</b>	18020	18024	18030
<b>High Range °F</b>	18021	18025	18031

	3-Day	10-Day	31-Day
<b>Low Range °C</b>	18022	18026	18028
<b>Low Range °F</b>	18023	18027	18029

DeltaTrak manufactures products under an ISO 9000 registered quality management system

- Highly visible LCD display and large window for viewing current and recently chart recorded temperature data
- Reusable, light weight, compact and battery operated, can be wall-mounted, or hung from a loop
- Wall-mounting bracket, screws and QC chart provided
- 12 models in °F and °C scales and two temperature ranges for 3-Day, 10-Day, 31-Day and 62-Day time intervals

SS0033 13K1

