

Product Specifications

FlashLink Electronic Data Logger



External Temp Sensor Range	-40°F to 302°F (-40°C to 150°C)
Temperature Accuracy	±1°F (0.5°C) at 32°F to 150°F (0°C to 66°C) ±2°F (1°C) over the entire range
Temperature Resolution	0.1°F/C
Logged Data Capacity	7,918 data points
Data Download Time	5 second typical for 3,800 data points
Programmable Alarm Levels	High and low levels over entire range
Startup Alarm Delay	Skip 1 to 16 points
Operating Alarm Delay	0 to 79 minute delay filter
Logging Time Interval Range	3 seconds to 24 hours
Programmable Delayed Start	1 second to 256 days
LED Indicators	12 second flashing red for alarm; green for active
Battery Type/Life	CR2450 3v lithium / 1 year
Dimensions / Enclosure	ABS plastic case, 3.25" x 2.25" x .75" (8.3 x 5.7 x 1.9 cm)
Water Resistance	Withstands immersion up to six inches
Shock Resistance	Withstands 3 foot drop to hard surface
Certification	CE Mark by T.U.V.; Calibration traceable to N.I.S.T.
Min. System Requirements	PC with 4 MB RAM, Windows XP or Vista
Software Requirements	FlashLink Program Manager Software
Min. System Requirements	IBM compatible 486 with 4MB RAM, Windows XP or Vista
Software Requirements	FlashLink Program Manager Software #20223



Model 20204

- Two sharp-tip external stainless steel temperature probes 3.5 in(89mm) with 40 in.(1m) cable
- Very easy to use and highly accurate
- Output charts, graphs, spreadsheets or email your results anywhere in the world

DeltaTrak manufactures products under an ISO 9000 registered quality management system

SS0053 13K1

