

Product Specifications

FlashLink Mini Multi-Use Data logger



Operating Range	-40°F to 150°F (-40°C to 66°C)
Temperature Accuracy	±1.0°F (0.5°C) From 32°F to 150°F (0°C to 66°C) ±2.0°F (1.0°C) over entire range
Temperature Resolution	0.1°F/°C
Data Capacity	3,823 data points
Data Download Time	5 seconds
Programmable Alarm Levels	High and Low levels over entire range
LED Indicators	Flashing red for alarm, green for active
Battery Type	Lithium Coin cell
Dimensions/Enclosure	2.68 in L x 1.27 in W x 0.45 in H; (68.07mm L x 32.25mm W x 11.43mm H); ABS plastic case
Weight	0.64 oz. (18.14g)
Certification	CE Mark, NIST traceable, RoHS compliant
System Requirements	Windows PC with current operating system, Adobe Reader
Programming	FlashPDF Program Manager software
Download Requirements	8-Pin to USB Adapter



Model 30024

- Ideal for documenting storage and transport conditions of temperature sensitive products
- User Programmable: manual or automatic start, sample interval, alarm limits, data tags
- Easily downloads to a PC using 8-Pin to USB Adapter

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS0143 16C2

