

Product Specifications

FlashLink PDF Multi-Use Data Logger



Measurement Range	-40°F to 122°F (-40°C to 50°C)
Temperature Resolution	0.2°F /0.1°C
Accuracy	±1.0°F from -4°F to 113°F; (±0.5°C from -20°C to 45°C) ±2.0°F above 113°F; (±1.0°C above 45°C) ±2.0°F below -4°F; (±1.0°C below -20°C)
Data Capacity	16,112 points
Sample Interval	5 minutes
Data Download Time	30 seconds typical
Factory Programmable Alarm Limits	High/low limits over entire temp range
Battery	Coin Cell Lithium battery
Dimensions	1.93" x 3.62" x 0.67" (49mm x 92mm x 17mm)
Casing	ABS plastic
Weight	1.6 oz. (45.36 grams)
Shock Resistance	Withstands 3-foot (1 meter) drop to hard surface
Certification	CE Mark, Calibration traceable to NIST, ROHS Compliant, BSS 7061 Compliant
Display	LCD, Red LED Alarm
Storage Conditions	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
PDF Standards	Complies with ISO19005-1, PDF/A, 21 CFR Part 11
System Requirements	Windows PC with current operating system Adobe Reader
Download Requirements	Direct USB connection



Models	
°F	40202
°C	40203

- One unit can be used multiple times
- No software or PC needed to program logger
- No software needed to download data
- Built-in USB connector, no special reading devices required
- Stops recording after downloading data
- Automatically creates secure PDF report and CSV file
- Push-button resets and restarts unit for next use
- Temperature statistics available on LCD
- Service available to custom configure logging parameters, alarms, delayed start

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

